

US006215920B1

(12) United States Patent

Whitehead et al.

(10) Patent No.: US 6,215,920 B1

(45) **Date of Patent:** Apr. 10, 2001

(54) ELECTROPHORETIC, HIGH INDEX AND PHASE TRANSITION CONTROL OF TOTAL INTERNAL REFLECTION IN HIGH EFFICIENCY VARIABLE REFLECTIVITY IMAGE DISPLAYS

(75) Inventors: Lorne A. Whitehead; Dmitri Nikolaevich Grandmaison; Robin John Noel Coope; Michele Ann Mossman; Andrzej Kotlicki, all of

Vancouver (CA)

(73) Assignee: The University of British Columbia,

Vancouver (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/324,103

(22) Filed: Jun. 2, 1999

Related U.S. Application Data

(63) Continuation-in-part of application No. 09/133,214, filed on Aug. 13, 1998, now Pat. No. 6,064,784, and a continuationin-part of application No. 08/872,161, filed on Jun. 10, 1997, now Pat. No. 5,959,777.

(51) Int. Cl.⁷ G02B 6/26

618, 831, 833; 349/63, 159; 362/554, 556,

(56) References Cited

U.S. PATENT DOCUMENTS

3/1971	Myer .
10/1971	Rajchman .
10/1972	Tellerman.
5/1973	Castegnier .
	10/1971 10/1972

3,746,785	7/1973	Goodrich .
3,796,480	3/1974	Preston, Jr. et al
3,987,668	10/1976	Popenoe .
4,148,563	4/1979	Herbert .
4,165,155	8/1979	Gordon, II et al
4,218,302	8/1980	Dalisa et al

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

4343808A1 6/1995 (DE).

OTHER PUBLICATIONS

3M FluorinertTM Electronic Liquid brochure, http://www.3m.com/fluids/florinrt.html, Sep., 1998.

"Patented fiber switch revs speed, cuts cost", George Kotelly, in "Lightwave" Oct., 1995 web site publication of PennWell Publishing Co., Tulsa, OK.

"Evanescent—wave scattering by electrophoretic microparticles: a mechanism for optical switching", Remillard et al, Applied Optics, vol.34, No.19, Jul. 1, 1995, pp.3777–3785.

Primary Examiner—Phan T. H. Palmer (74) Attorney, Agent, or Firm—Oyen Wiggs Green & Mutala

(57) ABSTRACT

Charged particles suspended in a medium such as Fluorinert™ Electronic Liquid are used to electrophoretically control total internal reflection (TIR) at a retro-reflective surface formed on a high refractive index material. Prismatic structures redirect ambient light from an overhead light source toward a display image and then from the image to the region in front of the image, yielding a high contrast reflective display. A transparent planar waveguide front lights the display with sequential flashes of red, blue and green light to generate a full color display. TIR can also be controlled at retro-reflective surfaces by means of a vaporliquid phase transition, or by changing the absorption coefficient of a material using electrical, chemical and/or electrochemical methods.

60 Claims, 8 Drawing Sheets

